## **TECHNICAL DATA**

#### Version 9

# AT202 Advance Gaffa® Satin Cloth Tape

## **General Description**

A polycloth extruded tape with white pressure sensitive, Aggressive, solvent free rubber-resin adhesive.

- Satin Finish
- Easy unwind and very easy tear
- · Cable friendly and clean peel adhesive
- Wide colour Range
- Can be written on
- Wide temperature range
- Water Resistant in situ
- Good abrasion resistance
- Comfortable to Awkward shapes
- Non-corrosive Adhesive



### **Technical Details**

Typical Values

Thickness	0.22mm
11110111033	0.2211111

Breaking load 33 N/cm

Elongation 13%

Adhesion

Steel 5.5 N/cm

Self 3.5 N/cm

Moisture Vapour permeability 20g/m²/24hrs

Water Extract

pH 6.0 to 8.0

Chloridemax 0.01% as NaCL

Sulphatemax 0.01% as Na2So4

RoHS Compliant Yes

Service Temperature -50°C to +80°C

Application Temperature +10°C to +45°C

Storage Temperature +12°C to +25°C

#### NOTE

Except where indicated otherwise, the figures stated are typical values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Information Sheet produced by the company for this product, which is available on request.

## STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.





#### AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

Adding more to adhesive tape

Advance Tapes International Limited Westmoreland Avenue Thurmaston Leicester LE4 8PH

England

Tel. +44 (0)116 251 0191 Fax. +44 (0)116 265 2046 contact@advancetapes.com

www.advancetapes.com