TECHNICAL DATA

Version 6

AT302 Double Sided Cotton Cloth Tape

General Description

A cotton cloth coated on both sides with a clear, hot-melt (synthetic rubber) plasticiser free adhesive interleaved with a yellow siliconised paper release liner.

- High tack
- Good adhesion
- Conformable to awkward shapes
- Easy tear



Technical Details

Typical Values

Tape thickness (Excluding liner) 0.25mm

Release liner weight 80gsm

Breaking Load 22 N/cm

Elongation 4%

Adhesion to Steel

Faced Side 20.0 N/cm

Unfaced Side 20.0 N/cm

RoHS compliant Yes

Service Temperature -10°C to +50°C

Application Temperature +10°C to +30°C

Max Service Temp (Short term) -20°C to +65°C

Storage Temperature +12°C to +25°C

NOTE

Except where indicated otherwise, the figures stated are typical values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Information Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.





AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.