

TECHNICAL DATA

Version 6

AT395 Reverse Wound Double Sided Transfer Tape

General Description

A clear solvent acrylic reinforced with fibreglass on a brown siliconised paper release liner. Supplied on a 25mm plastic core to fit a hand held dispenser.

- High temperature resistance
- UV resistant
- Humidity resistant
- High tack

Technical Details

Typical Values

Adhesive thickness	0.04mm
Release liner weight	80gsm
Release liner thickness	77 µm
Adhesion to steel	
Faced side	3.5 N/cm
Unfaced side	3.5 N/cm
RoHS compliant	Yes
Service Temperature	-10°C to +100°C
Application Temperature	+15°C to +30°C
Max Service Temp (short term)	-20°C to +130°C
Storage Temperature	+12°C to +25°C



NOTE

Except where indicated otherwise, the figures stated are typical values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Information Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.



AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

Adding more to adhesive tape

Registered in England No. 929843
Vat No. 115-6143-00

Advance Tapes International Limited
Westmoreland Avenue
Thurmaston
Leicester LE4 8PH
England

Tel. +44 (0)116 251 0191
Fax. +44 (0)116 265 2046
contact@advancetapes.com

www.advancetapes.com