TECHNICAL DATA

Version 7

AT536 35 Micron Tin Clad Copper Shielding Tape

General Description

35 micron tin clad copper foil coated with an electrically conductive thermosetting solvent based acrylic adhesive supplied on a removable silicone liner.

- · Conductive acrylic adhesive
- Good high and low temperature resistance
- Excellent resistance to ozone, oil, chemicals and water
- Easily soldered
- Easy unwind

Specification

Tested in accordance with ASTM D-1000 latest issue, BS EN 60454 - Part 2 test methods (formerly VDE 0340, BS 3924).

Construction is tested in-house and conforms to the Flame retardant requirement part only of UL510



Typical Values	BS value	ASTM value
Foil thickness Adhesive thickness Total thickness	0.035mm 0.025mm 0.060mm	1.4 mil 1.0 mil 2.4 mil
Adhesion to steel	5.0 N/cm	45 oz/inch
Tensile strength	40 N/cm	22 lbs/inch
Elongation	5%	5%
Temperature resistance	-20°C to +155°C	+311°F

Electrical resistance through

Adhesive* 0.003 ohms

RoHS compliant Yes

Storage Temperature +12°C to +25°C



NOTE

Except where indicated otherwise, the figures stated are typical values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Information Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.





AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

^{*} Tested according to MIL STD 202F method 307 across surface area of 1 sq. inch.

^{*}Standard charge for certificate: £25.00.