TECHNICAL DATA

Version 8

AT220 Advance Gaffa® Exhibition Floor Tape

General Description

A semi matt conformable polythene coated cloth tape coated with an aggressive, solvent free rubber-resin, peel clean thermosetting adhesive.

- Peel clean after 7 days in situ
- Easy tear and controlled unwind
- Water resistant in situ
- Conformable to awkward shapes
- · Good abrasion resistance
- Non-corrosive adhesive
- Writable surface



Technical Details

Typical Values

Thickness 0.27mm

Breaking Load 50 N/cm

Elongation 30%

Adhesion

Steel 3.0 N/cm

Self 1.5 N/cm

RoHS compliant Yes

Service Temperature -50°C to +110°C

Application Temperature +5°C to +45°C

Storage Temperature +12°C to +25°C

NOT

Except where indicated otherwise, the figures stated are typical values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Information Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.



AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.